

HIGH GLOSS COLLECTION

—by Somerset—



						
NATURAL RED OAK Red Oak	BUTTERSCOTCH Red Oak	GUNSTOCK Red Oak	CHERRY OAK Red Oak	NATURAL WHITE OAK White Oak	CHESTNUT White Oak	SHADOW Red Oak

APPALACHIAN OAK FLOORING
WITH A HIGHER GLOSS FINISH
WILL MAKE YOUR SPACE SHINE.



S SOLID
3/4" thick, random lengths up to 6-1/2'
WIDTHS: 2-1/4", 3-1/4"



PRODUCT SPECIFICATION SHEET

05/15

HIGH GLOSS: SOLID

S

Product:	Somerset High Gloss Collection Solid Hardwood Flooring			
Species:	Red Oak or White Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade			
Dimensions:	Thickness: 3/4"* Widths: 2-1/4", 3-1/4" Lengths: Random from 10" up to 6-1/2' *Nominal			
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with the National Wood Flooring Association.			
Profile:	Eased Edge, Square End			
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:		2¼" Width	3¼" Width	Species
	Natural Red Oak	PS2601HG	PS3601HG	Red Oak
	Butterscotch	PS2603HG	PS3603HG	Red Oak
	Gunstock	PS2604HG	PS3604HG	Red Oak
	Cherry Oak	PS2605HG	PS3605HG	Red Oak
	Natural White Oak	PS2606HG	PS3606HG	White Oak
	Chestnut	PS2607HG	PS3607HG	White Oak
	Shadow	PS2610HG	PS3610HG	Red Oak
Gloss Level:	High Gloss			
Janka Hardness:	Species	Lbs		
	Red Oak	1290		
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are available at www.somersetfloors.com			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			